

The Kino Flo Select **4BANK** System has won awards as well as the hearts of lighting artists around the world.

The reason: versatility.

The portable 4Bank displays a soft beam like that of bounced light, but with special features to control its spread and intensity. Custom electronics ensure bright, flicker-free light.

During any given production day, a 4Bank can work as a soft key on the talent, a ring light on the camera, a bluescreen source, a set practical or a fixture for underwater.

Need a different color? Change the lamps. No light stand? Just tape it to a wall. The list of applications goes on and on. It's no wonder the 4Bank System has become an indispensable lighting tool for motion picture and television production.



## Fixture Specifications

	Part Number	Dimensions	Weight w/Lamps	Lamps	Lamp Type
4ft 4Bank	CFX-4804	51.5" x 13" x 3.5" (w/6.5" barn doors) 1310mm x 330mm x 90mm (w/165mm barn doors)	10lb / 4.5Kg	4	F40 / T12
2ft 4Bank	CFX-2404	26.75" x 13" x 3.5" (w/6.5" barn doors) 700mm x 330mm x 90mm (w/165mm barn doors)	6.5lb / 2.75Kg	4	F20 / T12

## Ballast Specifications

	Part Number	Input Voltage	Output Frequency	Amperage	Lamp Switching	Output Switching	Size	Weight
Select/Ve 4Bank	BAL-405-S120	120VAC 50/60Hz	25kHz	F40/5A, F20/3.5A, F14/2.5A	4/Off/2	4ft/2ft	12.38" x 8.25" x 2.5" 315mm x 210mm x 64mm	5lb 2.2Kg
Select/ef 4Bank	BAL-400-F230	230VAC 50/60Hz	25kHz	F40/2.5A, F20/1.7A, F14/1.2A	4/Off/2	4ft/2ft	14.38" x 9.3" x 2.5" 360mm x 225mm x 64mm	6lb 2.7Kg

## Photometrics

	FOOTCANDLES	500	170	80	45	35	25
	FEET	2	4	6	8	10	12
	<b>4ft 4Bank*</b>						
	METERS	.6	1.2	1.8	2.4	3	3.6
	LUX	5400	1836	864	486	378	270
	FOOTCANDLES	325	90	45	30	18	13
	FEET	2	4	6	8	10	12
	<b>2ft 4Bank*</b>						
	METERS	.6	1.2	1.8	2.4	3	3.6
	LUX	3510	972	486	320	194	140

\* When the reflector is removed and the white backing is used, light output is reduced about 1/3 of an f-stop and the color temperature may drop about 100° Kelvin. Beam angles Horz/Vert: 100 degrees (where intensity drops to 1/3 of an f-stop of maximum). Values are approximate and are based on Kino Flo True Match lamps.

## Ordering Information

### 4Bank Systems

Order Code	Description
CFX-4804	4ft Fixture
CFX-2404	2ft Fixture
MTP-K41	Mounting Plate w/ 3/8" Pin
MTP-B41	Mounting Plate w/Receiver
X16-25	Extension, 25ft
X16-12	Extension, 12ft
BAL-405-S120	Select/Ve Ballast, 120VAC
BAL-400-F230	Select/ef Ballast, 230VAC

### 4Bank Components

Order Code	Description
FIX-4804	4ft Fixture Shell
FIX-2404	2ft Fixture Shell
HAR-4804	4ft Harness
HAR-2404	2ft Harness
LVR-4804-B	4ft Louver/Black
LVR-2404-B	2ft Louver/Black
LVR-4804-S	4ft Louver/Silver
LVR-2404-S	2ft Louver/Silver
MTP-L	Lollipop w/Pin
MTP-LB	Lollipop w/Receiver

### 4Bank Accessories

Order Code	Description
X16-A9	4Bank to Double Splitter
X16-A4	4Bank to Single Splitter
X09-A16	Double to 4Bank Combiner
X04-A16	Single to 4Bank Combiner
DFS-4804	4ft 4Bank Flozier
DFS-2404	2ft 4Bank Flozier

Details of mount, lamp connector, and lamp harness

