

Kino Flo's Select **DOUBLE** has become indispensable to cinematographers as an all-purpose fill source, and over the camera as an eye light.

The featherweight 4ft Double is often hand held. Turn the long narrow source like a wand and watch shadows disappear. The 2ft Double is often dropped behind set pieces at the last minute to dress up a shot.

A Double system comes complete with a remote ballast that can run lamps 75 feet away. The Double Ballast has switches to control lamps independently, and on high output or standard output. Lamps can even be removed from their fixture in seconds and built directly into sets.

Details of mount, lamp connector, and lamp harness



Fixture Specifications

	Part Number	Dimensions	Weight w/Lamps	Lamps	Lamp Type
4ft Double	CFX-4802	51.5 x 7.5 x 3.5" (w/6.5" barn doors) 1310mm x 190mm x 90mm (w/165mm barn doors)	7lb 3.2Kg	2	F40/T12
2ft Double	CFX-2402	26.75 x 7.5 x 3.5" (w/6.5" barn doors) 700mm x 190mm x 90mm (w/165mm barn doors)	4lb 1.8Kg	2	F20/T12

Ballast Specifications

	Part Number	Input Voltage	Output Frequency	Amperage	Lamp Switching	Output Switching	Size	Weight
Select/Ve Double	BAL-205-S120	120VAC 50/60Hz	25kHz	F40/2.6A, F20/1.8A, F14/1.4A	2/Off/1	4ft/2ft	8.5 x 8.13 x 2.5" 215mm x 210mm x 64mm	3.2lb 1.4Kg
Select/ef Double	BAL-200-F230	230VAC 50/60Hz	25kHz	F40/1.3A, F20/0.9A, F14/0.7A	2/Off/1	4ft/2ft	10.13 x 9.13 x 2.5" 250mm x 225mm x 64mm	4.1lb 1.8Kg

Photometrics

FOOTCANDLES		111	64	40	27	20
4ft Double*	FEET	4	6	8	10	12
	METERS	1.2	1.8	2.4	3	3.6
	LUX	1195	689	431	291	215
FOOTCANDLES		100	50	30	21	16
2ft Double*	FEET	4	6	8	10	12
	METERS	1.2	1.8	2.4	3	3.6
	LUX	1077	538	334	226	172

* When the reflector is removed and the white backing is used, light output is reduced about 1/3 of an f-stop and the color temperature may drop about 100° Kelvin. Beam angles Horiz/Vert: 100 degrees (where intensity drops to 1/3 of an f-stop of maximum). Values are approximate and are based on Kino Flo True Match lamps.

Ordering Information

Double Systems

Order Code	Description
CFX-4802	4ft Fixture
CFX-2402	2ft Fixture
MTP-K41	Mounting Plate w/ 3/8" Pin
MTP-B41	Mounting Plate w/ Receiver
X09-25	Extension, 25ft
X09-12	Extension, 12ft
BAL-205-S120	Select/Ve Ballast, 120VAC
BAL-200-F230	Select/ef Ballast, 230VAC

Double Components

Order Code	Description
FIX-4802	4ft Fixture Shell
FIX-2402	2ft Fixture Shell
HAR-4802	4ft Harness
HAR-2402	2ft Harness
LVR-4802-B	4ft Louver/Black
LVR-2402-B	2ft Louver/Black
LVR-4802-S	4ft Louver/Silver
LVR-2402-S	2ft Louver/Silver
MTP-L	Lollipop w/Pin
MTP-LB	Lollipop w/Receiver

Double Accessories

Order Code	Description
X09-A4	Double to Single Splitter
X09-A16	Double to 4Bank Combiner