

## **DIMMERMASTER 406D / 124D / 410D**



Listed for Compliance with UL 508 0 to +10VDC & DMX-512



The "shoebox" dimmers are very compact units with four 1000W dimmers. They may be pipe or tree mounted and are perfect for tight spaces where conventional rackmount dimmer packs are too bulky. The units accept DMX-512 control. Analog 0-10VDC control can be substituted as a factory option. The starting channel is set on a thumbwheel switch, which also provides load testing and local control. A status LED indicates the presence of a DMX control signal. With both male and female XLR connectors, the control signal may be daisy-chained from pack to pack. The DM-406 gets its power from a single standard 15 Amp wall outlet and has a maximum total capacity of 1800 watts.

## **FEATURES**

- DMX (0 to +10VDC control optional)
- 120V power input, 220V optional
- Motorbase inlet accepts standard extension cords.
- One U-ground (Edison) receptacle per channel
- Stage Pin output option available
- Thumbwheel starting channel select switch
- Non-dim, full-on, and DMX terminate switches
- Local control & load testing
- Signal present LED
- Dim. 6.75" X 5" X 3.75"
- Wt. 6 pounds
- One year warranty

## **SHOEBOX MODELS**

DM-124-DSP 1x2400w / 2400w Total Cap.

DM-406-SUG 4x1000w / 1800w Total Cap.

DM-406-SSP 4x1000w / 1800w Total Cap.

DM-410-SUG 4x1000w / 3600w Total Cap.

(30A twistlock on DM-410D)

(20A twistlock on DM-124D)

**Dove Lighting Systems, Inc.** 

3563 Sueldo Street Unit E San Luis Obispo, Ca 93401 +1 805 541 8292 fax +1 805 541 8293 dove@dovesystems.com / www.dovesystems.com