

# ZOT jr.

Light Source: 240 WATT LED

Ballast: Internal Electronic

Auto Switching

Beam Angle 12°-20°

AN INEXPENSIVE, EASY TO OPERATE FOLLOWSPOT  
FROM THE INDUSTRY LEADER



## FEATURES

240 WATT LED

2 LEVER ZOOM OPTICS

LYCIAN BUILT NICHROME IRIS

FINE FOCUS

FOLDING 3 LEGGED BASE

5 COLOR DICHROIC BOOMERANG

ULTRA QUIET

## BIG LIGHT IN A TINY PACKAGE

**NEVER BEFORE HAS A FOLLOWSPOT OFFERED THIS MUCH LIGHT OUTPUT FROM A PACKAGE THIS SMALL. LYCIAN HAS TAKEN THE ULTRA COMPACT MARKET BY STORM. ZOT jr OFFERS AMERICAN QUALITY AT AN IMPORT PRICE. QUIET & COOL THE ZOT jr LED IS PERFECT FOR BUDGET CONSCIOUS SCHOOLS, DJ'S, CLUBS AND ANYWHERE A VERY COMPACT FIXTURE IS REQUIRED**



Proudly Made in USA

Specifications subject to change without notice

LYCIAN STAGE LIGHTING PO BOX 214 SUGAR LOAF NY 10981 USA TEL. +1 (845) 469-2285 FAX +1 (845) 469-2285  
[www.lycian.com](http://www.lycian.com) [info@lycian.com](mailto:info@lycian.com)

# ZOT jr.

## Architect & Engineers Specifications

The luminaire is a 240 watt LED followspot. The spot diameter shall be controlled by a top mounted lever which opens and closes a nichrome steel iris. The unit shall include a top operated fader and a 5 color dichroic boomerang. A 240 watt LED with heat sink is housed in the rear of the head. Optical quality lenses complete the optical system. The ZOT jr. utilizes an electronic switching power supply. The power supply is integrated into the followspot head. A 12 foot power cord with NEMA 5-15 is included. The ZOT jr. ships with a Lycian manufactured folding tripod base. Units are cooled by a quiet low volume fan. The housing is constructed of extruded aluminum and cold rolled steel powder coated in black and red. The Lycian ZOT jr. will be specified. Only fixtures manufactured in the USA acceptable.

## ZOT jr. LED Photometrics

Distance Feet	20'	40'	60'	80'
Meters	6	12	18	25
Spot Dia Ft	4.3	8.6	12.9	17.2
Meters	1.3	2.6	3.9	5.2
Flood Dia. Ft	7	14	21	28
Meters	2.1	4.3	6.4	8.5
FC Spot	585	146	65	36
Lux Spot	6308	1572	700	388
FC Flood	252	63	28	16
Lux Flood	2713	678	301	172

Beam Angle 12°-20°

ZOT jr. Head Dimensions		Electrical Compatability	Order Code
Head Length	19-5/8"	100V-240V, 50 & 60 Hz Auto Switching	ZOT jr. Ships with head inc. connector, power cord, yoke and folding tripod. base
Max. Width w/ controls	10-7/8"		
Head Depth	13"		